

1. Identification

Product Identifier: **ISO15
ISO19
BC-2001 Mahogany Adhesive Part A
BC-8400 Urethane Elastomer Part A
UR-150 Polyurea Spray Elastomer Part A
DP11-83 Pink Urethane Elastomer Part A**

Product Code(s): BCISO15, BCISO19, BC8400A, BCUR150A

Use: Component for Mold Making and Casting. For Industrial/Professional use only.

Manufacturer: Polytek Development Corp.
55 Hilton Street, Easton, PA 18042

Phone Number: 610-559-8620 (8 a.m. to 6:30 p.m. EST)

Emergency Phone: CHEMTREC 800-424-9300 or +1 (703) 527-3887

E-mail: sds@polytek.com

2. Hazards Identification

GHS Classification:

- Acute Toxicity – Inhalation – Category 4
- Skin Irritation – Category 2
- Eye Irritation – Category 2B
- Respiratory Sensitization – Category 1
- Skin Sensitization – Category 1
- Specific Target Organ Toxicity Single Exposure – Category 3
- Specific Target Organ Toxicity Repeat Exposure – Category 2

Label Elements: Danger



Hazard Phrases:

- H315 Causes skin irritation.
- H320 Causes eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to lungs through prolonged or repeated exposure by inhalation.

Precautionary Phrases:

- P260 Do not breathe vapors.
- P261 Avoid breathing vapors.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves.
- P284 In case of inadequate ventilation, wear respiratory protection.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P317 Get medical help.
- P319 Get medical help if you feel unwell.
- P332+P317 If skin irritation occurs: Get medical help.
- P333+P317 If skin irritation or rash occurs: Get medical help.
- P362+364 Take off contaminated clothing and wash before reuse.
- P337+P317 If eye irritation persists: Get medical help.

- P342+P316 If experiencing respiratory symptoms: Get emergency medical help immediately.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P403+233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents and container in accordance with local, regional and national regulations.

Supplemental Information: Individuals sensitized to isocyanates should discontinue use. Long-term overexposure to isocyanates may cause lung damage.

This is one part of a two-part system. Read and understand the hazard information on part B before using.

3. Composition/Information on Ingredients

Chemical Name	CAS #	%
4,4'-methylenediphenyl diisocyanate	101-68-8	60-70%
Other ingredients are not classified as health, physical or environmental hazards, or are present below cut-off/concentrations limits.		

4. First-Aid Measures

- Eye Contact:** Rinse thoroughly with water for at least 15 minutes, holding the eyelids open to be sure the material is washed out. Get prompt medical attention.
- Skin Contact:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use. Discard items that cannot be decontaminated.
- Inhalation:** Do not breath vapors. If inhales, remove person to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.
- Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Get medical attention.
- Most Important Symptoms/Effects:** Causes skin and eye irritation. Vapors may cause respiratory irritation. May cause allergic skin and/or respiratory reaction in sensitized persons. Symptoms include skin rash, wheezing, shortness of breath and other asthma symptoms. Prolonged inhalation overexposure may damage the lungs and respiratory system.
- Indication of Immediate Medical Attention/Special Treatment:** Immediate medical attention is required for asthmatic symptoms or serious inhalation exposures. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Persons sensitized to isocyanates should not use this product.

5. Fire-Fighting Measures

- Extinguishing Media:** Use foam, carbon dioxide or dry chemical. Do not use solid water stream. Solid stream of water into hot product may cause violent steam generation or eruption.
- Specific Hazards:** Not classified as flammable or combustible. Product will burn under fire conditions. Do not allow run-off from fire-fighting to enter drains or waterways.
- Special Protective Equipment & Precautions for Fire-Fighters:** Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Remove all ignition sources. Clear non-emergency

personnel from the area. Wear appropriate protective clothing to prevent eye and skin contact and avoid breathing vapors. Ventilate area. Caution – spill area may be slippery.

Methods and Materials for Containment and Cleanup: Cover with an inert absorbent material and collect into an appropriate container for disposal. Do not seal the container since CO₂ is generated on contact with moisture and dangerous pressure buildup can occur. Decontaminate floor area with a mixture of water plus isopropyl alcohol (20%), household ammonia (10%), and detergent (2%). Do not allow discharge to enter waterways.

7. Handling and Storage

Safe Handling: Avoid breathing vapors, aerosols and mists. Use with properly positioned local exhaust ventilation to prevent exposure. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep container closed when not in use. Persons susceptible to skin sensitization problems or asthma allergies, chronic or recurrent respiratory disease should not use this product.

Safe Storage: Store indoors at temperatures between 55°F and 95°F. Store in original, unopened containers. Protect from atmospheric moisture and water since isocyanates react with water to form CO₂ leading to potentially dangerous pressure build up in sealed containers.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits:

Chemical Name	Exposure Limits
4,4'-methylenediphenyl diisocyanate	0.005 ppm TWA ACGIH TLV 0.02 ppm (C) OSHA PEL

Ventilation: Use with properly positioned local exhaust ventilation to prevent exposure and maintain air levels below the occupational exposure limits.

Respiratory Protection: If ventilation is not adequate, use an approved respirator with organic vapor cartridges or supplied air. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

Skin Protection: Wear impervious gloves, such as butyl rubber or nitrile rubber.

Eye Protection: Wear chemical safety goggles.

Other Protective Measures: Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and Chemical Properties

Appearance: Clear liquid

Odor: Mild odor

Odor Threshold: No data available

pH: Not applicable

Melting Point/Freezing Point: No data available

Boiling Point: No data available

Flash Point: No data available

Evap. Rate: No data available

Flamm. Limits: No data available

Vapor Pressure: No data available

Vapor Density: No data available

Relative Density: 1.12 @ 25°C

Solubility: Insoluble in water

Partition Coefficient: n-octanol/Water: No data available

Auto-Ignition Temp: No data available

Decomposition Temp: No data available

Viscosity: 1,000-1,200 cps

10. Stability and Reactivity

Reactivity: Isocyanates react with many chemicals, including alcohols and amines, and the rate of reaction increases with temperature.

Reaction with water generates carbon dioxide and heat.

Chemical Stability: Stable under recommended conditions.

Possibility of Hazardous Reactions: Elevated temperatures can cause hazardous polymerization. Polymerization can be catalyzed by strong bases or water. Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.

Conditions to Avoid: Avoid moisture and temperatures below 55°F and above 95°F to protect product integrity and prevent pressure buildup in closed containers.

Incompatible Materials: Avoid contact with water, acids, bases, amines, and some metals (e.g., copper and copper alloys).

Hazardous Decomposition Products: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke, Hydrogen cyanide (hydrocyanic acid).

11. Toxicological Information

Eye Contact: May cause eye irritation.

Skin Contact: Causes skin irritation. Skin contact may cause an allergic skin reaction. Animal studies indicate that skin contact with isocyanates may affect potential respiratory sensitization.

Inhalation: At room temperature, vapors are minimal due to low volatility. Vapors or aerosols (e.g., generated during heating or spraying) may cause respiratory irritation and possibly pulmonary edema. May cause respiratory sensitization. For individuals sensitized to isocyanates, exposure may result in allergic respiratory reactions (e.g., coughing, wheezing, difficulty breathing).

Ingestion: Single oral dose toxicity is low. Ingesting large amounts may cause adverse gastrointestinal effects.

Chronic Health Effects: Repeated or prolonged exposure to isocyanates above exposure limits may cause an allergic sensitization of the respiratory tract causing an asthma-like response upon re-exposure. Repeated overexposure to isocyanates has been associated with decreased lung function. Repeated or prolonged dermal contact with this product may cause allergic skin sensitization in some individuals.

Acute Toxicity Values: No toxicity data is available for this product. For 4,4'-methylenediphenyl diisocyanate (CAS 101-68-8):

Oral LC50 Rat: >5,000 mg/kg

Dermal LC50 Rat: >9,400 mg/kg

Inhalation LC50 Rat: 0.49 mg/L 4 hr (dust/mist)

Respiratory Sensitization: Isocyanates are respiratory sensitizers.

Skin Sensitization: Isocyanates are skin sensitizers.

Germ Cell Mutagenicity: Product has not been tested for mutagenicity. No ingredients are classified as mutagens.

Carcinogenicity: Product has not been tested for carcinogenicity. No ingredients are designated as carcinogens by NTP, IARC, or OSHA.

Reproductive Toxicity: Product has not been tested for reproductive toxicity. No ingredients present above cut-off levels are classified as reproductive toxins.

Specific Target Organ Toxicity:

Single Exposure: May cause respiratory irritation.

Repeat Exposure: After repeated exposure, isocyanates may cause respiratory irritation and lung damage.

12. Ecological Information

Ecotoxicity: No data available. Do not release into waterways.

Persistence and Degradability: No data available.

Bioaccumulative Potential: Isocyanates are not expected to bioaccumulate.

Mobility in Soil: No data available.

13. Disposal Considerations

Dispose according to local, state and federal regulations. Upon exposure to moisture, product forms an inert, non-hazardous solid.

14. Transport Information

U.S. DOT: NA3082, Other regulated substances, liquid, n.o.s. (MDI), 9, PG III.

Reportable Quantity (RQ): 5000lbs.

IMDG: Not regulated for transport.

AIR/IATA: Not regulated for transport.

Emergency Shipping Information: Call CHEMTREC, 800-424-9300 or +1-703-527-3887

15. Regulatory Information

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: RQ for MDI is 5000 lb. Some States have more stringent requirements. Report spills in accordance with local and state regulations.

SARA TITLE III Section 311/312: Acute Health, Chronic Health

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

4,4'-methylenediphenyl diisocyanate (CAS 101-68-8) 60-70%

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

STATE REGULATIONS:

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

16. Other Information

Training Advice: All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

Recommended Uses and Restrictions: This product is intended for industrial use only.

SDS Revision Notes: GHS Format, November 12, 2019

Disclaimer: The information contained herein is considered accurate; however, Polytek Development makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.